


**shower underlay DallFlex Floor Plan D, DN 40, 0,9 x 0,9 m**

Product No. **540089**  
 EAN: 4001636540089  
 Discount group: 11



with drain point positioned near the wall for installation with CeraFloor shower channels.

Outlet DN 40 horizontal, can be positioned on three sides without tools, with ball-joint, adjustable 0 – 15 degrees

specification:

- DallFlex Plan drain body system
- flexible sealing collar for secure bonding of under-tile waterproofing
- removable trap insert with 30 mm water seal
- temporary blanking plate
- suitable for wheelchairs if tile size > 5 x 5 cm

material:

expanded polystyrene (EPS), top side reinforced with glass fibre fabric and lined with waterproof fleece; drain body made of highly impact-resistant polypropylene; outlet polyethylene, weldable

Product No.	Description	Dimensions
535511	trap insert DallFlex Plan	

Product No.	Description	Dimensions
537546	shower channel CeraFloor Individual anthracite matt, 800-1500 mm	800-1500 mm

## 04. calendar\_month\_january 2020

537744	shower channel CeraFloor Individual brass matt, 800-1500 mm	800-1500 mm
537645	shower channel CeraFloor Individual red gold matt, 800-1500 mm	800-1500 mm
537478	shower channel CeraFloor Individual, 800-1500 mm	800-1500 mm
538208	shower channel CeraFloor Pure, 900 mm	900 mm
538253	shower channel CeraFloor Select anthracite matt, 900 mm	900 mm
538390	shower channel CeraFloor Select brass matt, 900 mm	900 mm
538321	shower channel CeraFloor Select red gold matt, 900 mm	900 mm
538123	shower channel CeraFloor Select, polished stainless steel, 900 mm	900 mm
538024	shower channel CeraFloor Select, satin stainless steel, 900 mm	900 mm
540393	supportset shower underlay DallFlex, 900 x 900 mm	900 x 900 mm