


floor drain DallDrain Select OM, DN 50, 100 x 100 mm

Part number: 517555 GTIN: 4001636517555 Rebate group: 6





Description:

floor drain DallDrain Select OM, DN 50, 100 x 100 mm conforming to DIN EN 1253 $\,$

Floor drain including grating DallDrain Select with stainless steel grate in stainless steel frame. Side outlet DN 50, with ball joint, adjustable from 0 – 15 degrees.

Specification

- Stainless steel grate and frame
- Integrated screed anchoring
- Flexible, click-in sealing sleeve for secure connection to bonded and sheet waterproofing conforming to DIN 18534
- Fully removable, two-piece trap insert and rodding eye, 50 mm water seal (conforming to DIN EN 1253))
- Temporary blanking plate
- Spigot can be shortened for floorings 10 36 mm (including adhesive)

Material

Polypropylene drain body and outlet, highly impact-resistant; 1.4301 stainless steel grate, load class K 3 (300 kg); spigot in ABS, frame in 1.4301 stainless steel

Pre-assembled set consisting of parts no. 517265 + 517210.

Grating with positioning aid laterally adjustable +/- 2.5 mm.

Flow rates tested to DIN EN 1253:

Nominal diameter	Product stan- dard	Min. flow rate according to norm	Water level according to norm	Flow rate at water level 10 mm	Flow rate at water level 20 mm
DN 50	DIN EN 1253		20.00 mm	0.65 l/s	0.92 l/s

Spare parts:

517265 grating DallDrain Select, 100 x 100 mm 517197 sealing sleeve DallDrain 517357 trap insert DallDrain

Dallmer GmbH + Co KG · Wiebelsheidestraße 25 · 59757 Arnsberg · Tel.: +49 2932 9616-0 · Fax: +49 2932 9616-222

www.dallmer.com · info@dallmer.de